

## Technical Specifications

<b>Video</b>	
Video Interface	HDMI
Single Link Range	480P,720i/p, 1080i/p
Video Data Rate	4.95 Gbps
Resolution	1920 x 1200 @ 60 Hz, Resolution up to 1280 x 1024 min. 75H
Power Supply	Universal Switch mode PSU (90-240V Input) 5VDC 1A
Input Interface	19 pin HDMI female type-A
<b>IR Input/output</b>	
Signal Type	30-100 kHz modulated IR
Connector	3.5 mm mini jack, Female



Optional Infrared Device

© Copyright 2008 Smart-AVI, All Rights Reserved

### Notice

The information contained in this document is subject to change without notice. Smart-AVI makes no warranty of any kind with regard to this material, including but not limited to, implied warranties of merchantability and fitness for any particular purpose.

Smart-AVI will not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance or use of this material.

No part of this document may be photocopied, reproduced or translated into another language without prior written consent from Smart-AVI.

For the complete manual, visit [www.smartavi.com](http://www.smartavi.com).

# Smart-AVI

Smart Audio Video Integration

## User Manual

### **HDX1000** *HDMI over twisted pair*



Extend HDMI display with IR control up to 330 feet away

**Smart-AVI**  
2840 N. Naomi Ave.  
Burbank, California 91504  
Phone: (818) 565-0011  
Facsimile: (818) 565-0020

[www.smartavi.com](http://www.smartavi.com)

